

LAUNCHER Continuously variable transmission fluid is a full synthetic lubricant based on carefully selected very high quality base oils that has been designed for most CVT gearboxes. It is suitable for most belts and chain-driven continuously variable transmissions. It offers outstanding anti-wear protection and stable friction characteristics.



APPLICATIONS

LAUNCHER Fully Synthetic CVT Fluid is formulated by carefully balancing base oils and advanced additives, to meet the requirements of both European and Japanese CVT manufacturers. This product may not be used in some hybrid vehicles, requiring special fluids.

PROPERTIES

LAUNCHER Fully Synthetic CVT Fluid provides outstanding metal-to-metal frictional properties and excellent protection and performance for CVTs throughout vehicle manufacturer-recommended drain intervals. It is Warranty Secure and will not void your vehicle's warranty. LAUNCHER Fully Synthetic CVT Fluid is a cost-effective, high-performance alternative to original equipment manufacturer (OEM) fluids.

PERFORMANCE FEATURES AND BENEFITS

- Outstanding thermal and oxidation stability.
- Active cleaning agents.
- Low volatility.
- Precisely balanced additive component system.
- Excellent anti-wear performance.
- Designed to provide excellent torque transfer.
- Excellent anti-shudder durability.
- Meets Industry Standards.
- Increased Wear Protection.
- Low-temperature Performance.
- Enhanced Fuel Economy.

RECOMMENDATIONS / SPECIFICATIONS

MEETS OR EXCEEDS :

AUDI /VW (TL 52180; G 052 180), Ford (CVT30/CVT23/Mercon C) , Subaru (Lineartronic CVTF), Honda (HCF-2), Nissan (NS-2), Mitsubishi (CVTF-J1), BMW Mini Cooper (EZL 799), Hyundai / Kia (SP-CVT 1), Suzuki (TC/NS-2/CVT Green 1), Dodge / Jeep (NS-2/CVT Green 1), Dodge /Jeep (NS-2/CVTF+4), GM /Saturn (DEX-CVT), Mercedes Benz (236.20).
Not recommended for hybrid CVT units (Toyota and Ford), Not for use in conventional automatic transmissions.

TYPICAL TECHNICAL PROPERTIES

PRODUCT CODE	LMOCVT
ASTM Colour	Light Orange
Density at 15.6°C, g/ml, ASTM D4052	0.8506
Kinematic Viscosity at 40°C, mm ² /s, ASTM D445	27
Kinematic Viscosity at 100°C, mm ² /s, ASTM D445	6
Viscosity Index, ASTM D2270	179
Flash Point (COC), ASTM D92	196 °C/384.8 °F
Pour Point, ASTM D97	-48 °C/ -54.4 °F
Brookfield viscosity at -40°C, mPa.s, ASTM D2983	12900

Note: These characteristics are typical of current production. While future production will conform to LAUNCHER'S specification, variations in these characteristics may occur.



Packing : 1L | 4L | 5L | 208L/Drum

Version : LL/TDS/CVT/V1/02-01-2023

Health and Safety: This lubricant, when used in accordance with our recommendations and for the application for which it is intended, does not constitute any special hazard. A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant