

SECTION 1: IDENTIFICATION				
Product trade name Company Identification	LAUNCHER High Performance Multigrade Motor Oil LAUNCHER AUTOMOTIVE (13893031 Canada Inc.) 55 Village Centre PI, Suite 200, Mississauga, ON L4Z 1V9, Canada			
Phone	+1 (905)804-1137			
Email	info@launcherautomotive.com			
Chemical family	Petroleum Lubricating Oil			
SECTION 2: Hazard Identification				
Eyes	Contact with eyes may cause minimal irritation, but practically non-irritating.			
Skin contact	Avoid skin contact. This product is slightly irritating. Repeated or prolonged contact with the skin could cause redness, itching, inflammation or cracking. Symptoms may include discolouration, swelling or a feeling of heat. Secondary infection. Avoid prolonged and/or repeated skin contact with used motor oils.			
Inhalation	Low toxicity. If less than one ounce is ingested, material may pass through the system without harm. On ingestion of large quantities, slight GI discomfort, diarrhea and headaches may occur.			
Ingestion	Low risk at ambient temperature. Prolonged breathing of vapour can cause headache, dizziness, nausea, respiratory irritation or chemical pneumonitis			
Medical conditions aggravated by exposure	Pre-existing dermatitis may be aggravated.			
SECTION 3: COMPOSITION OF INGREDIENTS				

Components	CAS number	Approximate Percentage Composition	Exposure limit
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil-unspecified	72623-86-0	70 - 90	5mg/m3 Mist
Performance Additives	Mixture	10 to 20	5mg/m3 Mist
Pour Depressant	Mixture	0.5 to 1.0	5mg/m3 Mist
Composition comments:	*CANADA GHS: The exact percentage (concentration) of composition has been withheld as a trade secret. US GHS: The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.		
	SECTION 4: FIR	ST-AID MEASURES	
Eye Contact	Immediately flush eyes with large amounts of water and continue flushing until irritation Subsides. If material is hot, treat for thermal burns and seek immediate medical attention.		
Skin contact	No treatment is necessary under ordinary circumstances. Remove contaminated clothing. Wash contaminated area thoroughly with soap and water. If redness or irritation occurs and persists, seek medical attention. If material is hot, submerge injured area in cold water. If victim is severely burned, remove to a hospital immediately.		
Inhalation	This material has a low vapour pressure and is not expected to present an inhalation exposure at ambient conditions.		
Ingestion	No treatment is necessary under ordinary circumstances. Do not induce vomiting. If victim Exhibits signs of lung aspiration such as coughing or choking, seek immediate medical assistance.		
Notes to physician	In case of skin injection, pro minimize necrosis and tissu	mpt debridement of the wound may be e loss.	e necessary to
		>MATERIAL	SAFETY DATA SHEET 1/4



SECTION 5: FIREFIGHTING MEASURES					
Fire classification	OSHA classification (29 CFR 1910.1200). Not classified by OSHA as flammable or combustible.				
Flash point Flammable limits	>200°C				
	Upper percent: N/A Lower percent: N/A				
Auto ignition temperature	No Data Available				
Extinguishing media	Use water fog, foam, dry chemical or carbon dioxide to extinguish flame.				
PROTECTION OF FIRE FIG	HTERS				
Instructions	This material will although it is not easily ignited. For fires involving this material, do not enter any enclosed or confined fire space without proper protective equipment, including self-contaminated breathing apparatus.				
combustion Product	Highly dependent on combustion conditions. A complex mixture of airborne solids, liquids and gases including Carbon Combustion products monoxide, carbon dioxide and unidentified organic compounds will be evolved when this materials undergoes combustion. Combustion may from oxides of: Calcium, Sulphur, Zinc, Boron, Molybdenum, and Nitrogen.				
	SECTION 6: ACCIDENTAL RELEASE MEASURES				
Personal precautions, protective equipment and emergency procedures	Keep out of low areas. Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. For personal protection, see section 8 of the MSDS.				
Environmental precautions	If the product contaminates rivers and lakes or drains inform respective authorities.				
Methods and materials for containment and	Stop the flow of material, if this is without risk.				
cleaning up	Large Spills : Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Use water spray to reduce vapors or divert vapor cloud drift. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.				
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean				
	surface thoroughly to remove residual contamination.				
	Never return spills to original containers for re-use. For waste disposal, see				
	section 13 of the MSDS.				
	SECTION 7: HANDLING AND STORAGE				
Precautions for safe	Use good industrial hygiene practices in handling this material. Avoid contact with				
Handling	eyes, skin and clothing. Do not handle until all safety precautions have been read and understood. Avoid prolonged exposure.				
Conditions for safe storage including any incompatibilities	Store in original tightly closed container. Keep away from heat, open flames or other sources of ignition. Store away from incompatible materials (see Section 10 of the MSDS). Keep out of reach of children.				



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION				
Exposure limit	This product does not contain any components with OSHA or ACGIH exposure limits.			
Eye/face protection	Eye protection is not required under conditions of normal use. If material is handled such that it could be splashed into eyes, wear plastic face shield or splash-proof safety goggles. No skin protection is required for single, short duration exposures. For prolonged or repeated			
Skin protection	exposures, use impervious clothing (boots, gloves, aprons, etc.) over parts of the body subject to exposure. If handling hot material, use insulated protective clothing (boots, gloves, aprons, etc.). Launder soiled clothes. Properly dispose of contaminated leather articles including shoes, which cannot be decontaminated.			
Respiratory protection	Respiratory protection is not required under conditions of normal use. If vapour or mist is generated when the material is heated or handled, use an organic vapour respirator with a dust and mist filter. All respirators must be NIOSH certified. Do not use compressed oxygen in hydrocarbon atmospheres. Consumption of food and beverage should be avoided in work areas where hydrocarbons are			
Personal hygiene	present. Always wash hands and face with soap and water before eating, drinking, or smoking. If vapour or mist is generated when the material is heated or handled, adequate ventilation in Accordance with good engineering practice must be provided to maintain concentrations below the specified exposure or flammable limits.			
Ventilation	The OSHA permissible exposure limit (PEL) and ACGIH threshold limit value (TLV) for oil mist is 5mg/m3. Chronic Other exposures below 5mg/m3 are without significant health risks. The ACGIH short-term exposure limit (STEL) for oil mist is 10mg/m3.			
	SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES			
Appearance	Clear and bright			
Colour	Amber			
Physical state	Liquid			
Vapour density (air = 1)	>1			
Boiling point	> 300 °C			
Melting point	N/A			
Specific Gravity @15°C	0.886 To 0.893 g/ml			
Viscosity @ 100°C	11.84 To 19.51 CST			
Viscosity @ 40°C	85.77 To 176.76 CST			
Solubility in water	Insoluble			
	CTION 10: STABILITY AND REACTIVITY INFORMATION			
Chemical stability	This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.			
Conditions to avoid	No Data Available.			
Incompatible materials to avoid	May react with strong oxidizing agents, such as chlorates, nitrates.			
Hazardous polymerisation	Hazardous polymerization will not occur.			
	SECTION 11: TOXILOGICAL INFORMATION			
Eye irritation	The eye irritation hazard is based on evaluation of data for similar materials or product components.			
Skin irritation	The skin irritation hazard is based on evaluation of data for similar materials or product components.			
Skin sensitization	No product toxicology data available.			
Acute dermal toxicity	The acute dermal toxicity hazard is based on evaluation of data for similar materials or product components.			
Acute oral toxicity	The acute oral toxicity hazard is based on evaluation of data for similar materials or product components.			
Inhalation toxicity	The inhalation toxicity is based on evaluation of data for similar materials or product compnents.			



SECTION 12: ECOLOGICAL INFORMATION				
Ecotoxicity	The toxicity of this material to aquatic organisms has not been evaluated. Consequently; this material should be kept out of sewage and drainage systems and all bodies of water.			
Environmental fate	This material is not expected to be readily biodegradable.			
SECTION 13: DISPOSAL INFORMATION				
Disposal methods	The product should not be allowed to enter drains, water courses or the soil.			
Waste from residues	Offer surplus and non-recyclable solutions to a licensed disposal company. Waste must be classified and labelled prior to recycling or disposal. Send to a licensed waste management company. Dispose of product residue in accordance with the instructions of the person responsible for waste disposal.			
SECTION 14: TRANSPORT INFORMATION				
International Regulations				
IATA-DGR	Not regulated as a dangerous good			
IMDG-Code	Not regulated as a dangerous good			
ADR/RID National Regulations	Not regulated as a dangerous good			
TDG	Not regulated as a dangerous good			
SECTION 15: OTHER INFORMATION				

REFERENCES: Sources of information used in preparing this MSDS included one or more of the following: results from in house or supplier toxicology studies, CONCAWE Product Dossiers, publications from other trade associations such as the EU Hydrocarbon Solvents, REACH Consortium, U.S. HPV Program Robust Summaries, the EU IUCLID Data Base, U.S. NTP publications, and other sources, as appropriate.

Issue date:	02-01-2023	
Version#:	1	
Effective date:	02-01-2023	
Prepared by:	LAUNCHER AUTOMOTIVE (13893031 Canada Inc.)	Phone: +1 (905)804-1137
Further Information:	Not Available	
Other Information:	For an updated MSDS, Please contact the supplier/manufacturer listed on the first page of the document.	

KEEP OUT OF REACH OF CHILDREN

REVISION STATEMENT

This revision corrects the product name .Other changes have been made throughout this Material Safety Data Sheet. Please read the entire documents.

DISCLAIMER OF WARRANTY

The above information contained herein is based upon data and information available to us, and reflects our best professional judgment. This product may be formulated in part with components purchased from other companies. In many instances, especially when proprietary or trade secret materials are used, Launcher's Products must rely upon the hazard evaluation of such components submitted by that product's manufacturer or importer. No warranty of merchantability, fitness for any use, or any other warranty is expressed or implied regarding the accuracy of such data or information, the results to be obtained from the use thereof, or that any such use do not infringe any patent. Since the information contained herein may be applied under conditions of use beyond our control and with which we may be unfamiliar, we do not ssumeresponsibility for the results of such application. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.